

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (currently amended) A semiconductor, comprising:
 - a semiconductor wafer having a plurality of integrated circuit chips thereon, such chips being separated by separating regions in the wafer, such wafer having a plurality of electrical contacts;
 - a self-supporting dielectric member having an electrical conductor thereon, such electrical conductor being elevated above the regions in the fractional portion of the wafer, such electrical conductor being electrically connected to the plurality of electrical contacts to electrically interconnect such plurality of chips, portions of the dielectric member with portions of the electrical conductor thereon spanning the regions in the wafer; and
 - a plurality of voltage generators, each one being associated with, and disposed adjacent to, a corresponding one of the chips.
2. (cancelled)
3. (currently amended) The semiconductor recited in claim 2 wherein each one of the voltage generators is disposed in the separating region.
4. (cancelled)
5. (cancelled)

6. (currently amended) A semiconductor, comprising:

a fractional portion of a semiconductor wafer having a plurality of integrated circuit chips thereon, such chips being separated by separating regions in the fractional portion of the wafer;

a plurality of sets of electrical components, each set being associated with, and adjacent to, a corresponding one of the chips; and

a self-supporting dielectric member having an electrical conductor thereon
electrically connecting the plurality of electrical selected one or ones of the electrical components to the chips with portions of the electrical conductor elevated above the regions in the fractional portion of the wafer and spanning the separating regions between the chips in the fractional portion of the wafer.

7. (previously presented) The semiconductor recited in claim 6 wherein each set of electrical components includes a plurality of different electrical components.

8. (withdrawn)

9. (withdrawn)

10. (withdrawn)

11. (currently amended) ~~The semiconductor recited in claim 6~~ A semiconductor, comprising:

a fractional portion of a semiconductor wafer having a plurality of integrated circuit chips thereon, such chips being separated by separating regions in the fractional portion of the wafer;

a plurality of sets of electrical components, each set being associated with, and adjacent to, a corresponding one of the chips; and

an electrical conductor electrically connecting the plurality of electrical selected one or ones of the electrical components to the chips with portions of the electrical conductor elevated above the regions in the fractional portion of the wafer and spanning the separating regions between the chips in the fractional portion of the wafer; and

wherein each one of the electrical components is disposed in the separating region.

12. (previously presented) The semiconductor recited in claim 11 wherein the electrical components are voltage generators.

13. (previously presented) The semiconductor recited in claim 12 wherein the voltage generators are interconnected by the conductor elevated above the regions in the fractional portion of the wafer.

14. (withdrawn)

15. (previously presented) The semiconductor recited in claim 12 wherein at least one of the voltage generators is coupled to more than one bus in corresponding ones of the plurality of integrated circuit chips.

16. (currently amended) A semiconductor package, comprising:

a fractional portion of a semiconductor wafer having a plurality of integrated circuit chips thereon, such chips being separated by regions in the fractional portion of the wafer, such fractional portion of the wafer having a plurality of electrical contacts;

a self-supporting dielectric member having an electrical conductor thereon, such electrical conductor being electrically connected to the plurality of electrical contacts to electrically interconnect such plurality of chips, portions of

the electrical conductor spanning the regions in the fractional portion of the wafer;
and

a plurality of voltage generators, each one being associated with, and
disposed adjacent to, a corresponding one of the chips.

17. (currently amended) ~~The semiconductor package recited in claim 16.~~ A semiconductor package, comprising:

a fractional portion of a semiconductor wafer having a plurality of
integrated circuit chips thereon, such chips being separated by regions in the
fractional portion of the wafer, such fractional portion of the wafer having a
plurality of electrical contacts;

a dielectric member having an electrical conductor thereon, such electrical
conductor being electrically connected to the plurality of electrical contacts to
electrically interconnect such plurality of chips, portions of the electrical
conductor spanning the regions in the fractional portion of the wafer; and
a plurality of voltage generators, each one being associated with, and disposed
adjacent to, a corresponding one of the chips; and

wherein each one of the voltage generators is disposed in the separating region.

18. (currently amended) A semiconductor package, comprising:

a fractional portion of a semiconductor wafer having a plurality of
integrated circuit chips thereon, such chips being separated by regions in the
fractional portion of the wafer, such fractional portion of the wafer having a
plurality of electrical contacts;

a self-supporting dielectric member having an electrical conductor thereon
electrically connected to the plurality of electrical contacts of the plurality of
chips to electrically interconnect such plurality of chips, portions of the electrical
conductor spanning the regions in the fractional portion of the wafer, such

conductor being elevated above the regions in the fractional portion of the wafer;
and

a plurality of voltage generators, each one being associated with, and
disposed adjacent to, a corresponding one of the chips.

19. (currently amended) The semiconductor package recited in claim ~~19~~ 18
wherein each one of the voltage generators is disposed in the separating region.

20. (currently amended) A semiconductor packaging arrangement, comprising:

(A) a printed circuit board having an electrical interconnect thereon;

(B) a semiconductor package, comprising:

(i) a fractional portion of a semiconductor wafer having a plurality of
integrated circuit chips thereon, such chips being separated by regions in
the fractional portion of the wafer, such fractional portion of the wafer
having a plurality of electrical contacts;

(ii) a self-supporting dielectric member having an electrical conductor
thereon electrically connected to the plurality of electrical contacts of the
plurality of chips to electrically interconnect such plurality of chips,
portions of the electrical conductor spanning the regions in the fractional
portion of the wafer; and

(iii) a plurality of voltage generators, each one being associated with, and
disposed adjacent to, a corresponding one of the chips; and

(C) a conductor for electrically connecting the electrical conductor of the package
to the electrical interconnect of the printed circuit board.

21. (currently amended) ~~The semiconductor packaging arrangement recited in claim 21~~ A semiconductor packaging arrangement, comprising:

(A) a printed circuit board having an electrical interconnect thereon;

(B) a semiconductor package, comprising:

(i) a fractional portion of a semiconductor wafer having a plurality of integrated circuit chips thereon, such chips being separated by regions in the fractional portion of the wafer, such fractional portion of the wafer having a plurality of electrical contacts;

(ii) an electrical conductor electrically connected to the plurality of electrical contacts of the plurality of chips to electrically interconnect such plurality of chips, portions of the electrical conductor spanning the regions in the fractional portion of the wafer; and

(iii) a plurality of voltage generators, each one being associated with, and disposed adjacent to, a corresponding one of the chips; and

(C) a conductor for electrically connecting the electrical conductor of the package to the electrical interconnect of the printed circuit board; and

wherein each one of the voltage generators is disposed in the separating region.

22. (new) The semiconductor recited in claim 1 wherein the self-supporting dielectric member is a printed circuit board.

23. (new) The semiconductor recited in claim 6 wherein the self-supporting dielectric member is a printed circuit board.

24. (new) The semiconductor package recited in claim 16 wherein the self-supporting dielectric member is a printed circuit board.

25 (new) The semiconductor package recited in claim 18 wherein the self-supporting dielectric member is a printed circuit board.

26. (new) The semiconductor packaging arrangement recited in claim 20 wherein the self-supporting dielectric member is a printed circuit board.